

# Vocal Microphones and Studio Microphones/Portable Amplifier System

## PDM-3

Order No. 0234850

### Dynamic vocal microphone

- Frequency response especially optimised for the vocal spectrum
- Low handling noise and high acoustic feedback suppression
- Robust design for a long life
- Supplied with connection cable

Model	PDM-3
Polar pattern	cardioid
System	dynamic
Audio frequency range	50-16,500 Hz
Nominal impedance	600 Ω
Sensitivity	1.8 mV/Pa
Max. sound pressure	147 dB
Housing material	diecast metal
Weight	315 g
Cable	XLR, bal., XLR, bal.
Connection	XLR, bal.



## PDM-57

Order No. 0234860

### Universal dynamic microphone

- For general sound pickup of instruments and for live performances
- Natural sound characteristics
- Characteristic sound with a high recognition value
- Supplied with connection cable

Model	PDM-57
Polar pattern	cardioid
System	dynamic
Audio frequency range	50-16,500 Hz
Nominal impedance	600 Ω
Sensitivity	1.8 mV/Pa
Max. sound pressure	145 dB
Housing material	diecast metal
Weight	250 g
Cable	XLR, bal., XLR, bal.
Connection	XLR, bal.



## CP-40

Order No. 0235250

**Replacement microphone head**, suitable for PDM-3 as well as microphones of the same design from other brand manufacturers.

