

## TG-10CH2

Order No. 0252670

**Charging station** for transmitters TG-10T/1 and receivers TR-10R/1 as well as for KA-10 components.

- For simultaneously charging rech. batteries of 2 devices
- Average charging time, depending on condition of rechargeable batteries used: approx. 8 hours
- Each slot with LED for indicating battery charging status

| Model        | TG-10CH2                                 |
|--------------|--|
| Suitable for | 2 x TG-10T/1, TG-10R/1, KA-10 components |
| Power supply | via encl. power supply                   |
| Dimensions   | 75 x 41 x 85 mm                          |
| Weight       | 485 g                                    |

- Mechanical reverse polarity protection
- Protection against overload, short-circuit and deep discharge

**Supplied w/o devices.**



## TG-10CH18

Order No. 0252660

**Transport case with integrated charging function**, for transmitters TG-10T/1 and receivers TG-10R/1 as well as for KA-10 components.

- For simultaneously charging rech. batteries of up to 18 devices
- Average charging time, depending on condition of rechargeable batteries used: approx. 8 hours
- Each slot with LED for indicating battery charging status

| Model        | TG-10CH18                                 |
|--------------|---|
| Suitable for | 18 x TG-10T/1, TG-10R/1, KA-10 components |
| Power supply | via encl. switch-mode power supply        |
| Dimensions   | 361 x 422 x 189 mm                        |
| Weight       | 3.26 kg                                   |

- Mechanical reverse polarity protection
- Protection against overload, short-circuit and deep discharge

**Supplied w/o devices.**



## TG-64CH18

Order No. 0259620

**Transport case with integrated charging function**, for transmitters and receivers of the TG-98 series as well as the TG-16 series.

- For simultaneously charging rech. batteries of up to 18 devices
- Average charging time, depending on condition of rechargeable batteries used: approx. 8 hours
- Each slot with LED for indicating battery charging status
- Mechanical reverse polarity protection

| Model        | TG-64CH18                                       |
|--------------|---|
| Description  | transport case with charging function           |
| Colour       | black   |
| Suitable for | 18 x TG-98RA/5, TG-98TA/5, TG-16RA/1, TG-16TA/1 |
| Power supply | via encl. switch-mode power supply              |
| Dimensions   | 362 x 422 x 189 mm                              |
| Weight       | 3.3 kg  |

- Protection against overload, short-circuit and deep discharge

**Supplied w/o devices.**



## TG-10CH36

Order No. 0252680

**Transport case with castors and integrated charging function**, for transmitters TG-10T/1 and receivers TG-10R/1 as well as for KA-10 components.

- For simultaneously charging rech. batteries of up to 36 devices
- Average charging time, depending on condition of rechargeable batteries used: approx. 8 hours
- Each slot with LED for indicating battery charging status
- Mechanical reverse polarity protection
- Protection against overload, short-circuit and deep discharge

| Model        | TG-10CH36                                 |
|--------------|---|
| Suitable for | 36 x TG-10T/1, TG-10R/1, KA-10 components |
| Power supply | via encl. switch-mode power supply        |
| Dimensions   | 400 x 561 x 230 mm                        |
| Weight       | 7.3 kg                                    |

- Robust hard-sided plastic transport case with carrying handle
  - Due to the integrated telescopic handle and 4 castors, the transport case can easily be pulled like a trolley
  - Can be locked via key
- Supplied w/o devices.**

